



# TYRE LEVER



The Roughneck Tyre Lever enables the quick and easy removal of pneumatic tyres. Manufactured from drop forged, heat treated alloy steel for exceptional strength and durability. Powder coated finish offers greater resistance to corrosion.

- Drop forged
- Heat treated
- Powder coated
- Size: 610mm/24"



DROP FORGED



HEAT TREATED



POWDER COATED

## PRODUCT OVERVIEW

CODE	DESCRIPTION	SIZE	WEIGHT	BARCODE	COMMODITY CODE
64-470	Tyre lever	610mm/24"	-	0 025997 644709	82055980 00

## ADDITIONAL INFORMATION

DESCRIPTION
-

## SINGLE ITEM DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (g)
64-470	596.0	35.0	-	1470.0

## PACKAGED ITEM DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (g)
64-470	596.0	35.0	-	1470.0

## WASTE PACKAGING DETAILS

OT CODE	PAPER & CARD (g)	PLASTIC (g)	METAL (g)
64-470	-	-	-

## INNER CARTON DIMENSIONS



# TYRE LEVER



OT CODE	LENGTH (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (g)	GROSS WEIGHT (g)	PACK QTY
64-470	-	-	-	-	-	6

## SHIPPING CARTON DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (g)	GROSS WEIGHT (g)	CARTON QTY
64-470	650	115	70	8.64	9.15	6

## PRODUCT SAFETY INFORMATION



WEAR EYE PROTECTION



WEAR HAND PROTECTION

## GUARANTEE



This ROUGHNECK® product includes a 25-Year Guarantee. This covers faulty materials or manufacturing defects, excluding normal wear and tear, consumable parts or customer misuse. Damaged or faulty items can be returned to the place of purchase for replacement. This guarantee is in addition to and in no way prejudices the users statutory rights.