



Manufactured from drop forged, heat treated steel for exceptional strength and durability. Mounted on a solid fibreglass core handle with a soft grip for added strength and comfort. Featuring milled convex striking faces with 45° chamfered edges to prevent chipping and damage to striking surfaces.

- Milled convex faces
- 45° chamfered edges
- Solid fibreglass core
- Soft grip
- Drop forged
- Heat treated
- Painted head





PRODUCT OVERVIEW

CODE	DESCRIPTION	SIZE	WEIGHT	BARCODE	COMMODITY CODE
65-608	Club hammer	-	1.4kg/3lbs	0 025997 656085	82052000 00
65-610	Club hammer	-	1.8kg/4lbs	0 025997 656108	82052000 00

ADDITIONAL INFORMATION

DESCRIPTION



CLUB HAMMERS



SINGLE ITEM DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (g)
65-608	253.0	110.0	-	1528.0
65-610	256.0	118.0	-	1908.0

WASTE PACKAGING DETAILS

OT CODE	PAPER & CARD (g)	PLASTIC (g)	METAL (g)
65-608	-	-	-
65-610	-	-	-

INNER CARTON DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (g)	GROSS WEIGHT (g)	PACK QTY
65-608	310.0	115.0	104.0	-	6.2	12
65-610	305.0	140.0	110.0	-	7.92	8

SHIPPING CARTON DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	DEPTH (mm)	NET WEIGHT (g)	GROSS WEIGHT (g)	CARTON QTY
65-608	360	330	130	18.69	19.18	12
65-610	325	280	134	16.0	17.0	8

PRODUCT SAFETY INFORMATION



WEAR EYE PROTECTION



WEAR HAND PROTECTION



WARNING: SERIOUS EYE OR BODILY INJURY MAY OCCUR FROM CHIPS OR FLYING FRAGMENTS. INSPECT TOOL BEFORE USE. DO NOT USE IF SIGNS OF CRACKS, CHIPS, MUSHROOMING OR LOOSE/DAMAGED HANDLES. STRIKE SQUARELY AND AVOID GLANCING BLOWS.

GUARANTEE



This ROUGHNECK® product includes a 25-Year Guarantee. This covers faulty materials or manufacturing defects, excluding normal wear and tear, consumable parts or customer misuse. Damaged or faulty items can be returned to the place of purchase for replacement. This guarantee is in addition to and in no way prejudices the users statutory rights.

PACKAGED ITEM DIMENSIONS

OT CODE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	WEIGHT (g)
65-608	253.0	110.0	-	1528.0
65-610	256.0	118.0	-	1908.0